

345

345



Pro-Line[®] Commercial Marine Finishes VINYL COPPER ANTIFOULING PAINT

1088C-01 BLUE

FOR PROTECTING UNDERWATER HULL SURFACES FROM MARINE FOULING
CQ1088C01 **822-4024**



ACTIVE INGREDIENTS	66.9%	EPA Reg. No.	577-025
Exempt Solvents	32.3%	EPA Est. No.	577-04-01
INERT INGREDIENTS	100.0%	577-04-02
Copper as Metallic	38.42%	577-04-03
CONTAINS PETROLEUM DISTILLATES	577-04-01

**KEEP OUT OF REACH OF CHILDREN
WARNING.**

**FLAMMABLE! VAPOR HARMFUL.
IRRITATES EYES, SKIN AND RESPIRATORY TRACT.**
See Side Panel For Additional Precautionary Statements.

1 U.S. Gal / 3.78 L

VOG: 387 g/L (2.55 lbs./gal.)

The Sherwin-Williams Company
151 Prospect Avenue
Cleveland, Ohio 44115
©2007 Sherwin-Williams Company

DIRECTIONS FOR USE

This is a violation of Federal law to use this product in a manner inconsistent with its labeling. This label must be in the possession of the user at the time of pesticide application.
FOR MORE DETAILED INSTRUCTIONS CONTACT THE SHERWIN-WILLIAMS COMPANY.
THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND WASTURE BEFORE APPLICATION OF PRIMER OR ANTI-FOULING PAINTS.

RECOMMENDED PRIMERS: 3000 Series, 4000 Series, 5000 Series and 4018 Epoxy Primer. Apply one or more coats of epoxy primer at a minimum of 4 dry mils per coat. Anti-fouling must be applied to final coat of epoxy while epoxy is still tacky. When epoxy can be touched firmly with the fingertips leaving an impression without having any of the epoxy adhering to the fingertips, proper adhesion will be achieved.

OLD ANTI-FOULING: This product may be applied over most lightly adhering anti-fouling paints. If old anti-fouling is questionable, perform adhesion test. **DO NOT APPLY OVER SOFT SLIDING-TYPE ANTI-FOULING PAINTS.**

REcoat TIME: 2 hour minimum, if epoxy applied. Otherwise, 4 hour minimum. No maximum between anti-fouling paints.

APPLICATION: Apply by conventional or airless spray. Stir well before using. **NOTE:** Anti-fouling paints are designed to be applied at 3 to 5 dry mils or 5 to 8 wet mils per coat. If anti-fouling paint is not applied at proper mil thickness, effectiveness of the coating will be reduced.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide that can not be used according to label instructions must be disposed of according to Federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL: Non-refillable container. Do not reuse or refill this container. Offer for recycling, if available, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

FIRST AID

IF SWALLOWED: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything to the person. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF IRRITATED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. **HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.**

Note to Physician

Contains petroleum distillate - vomiting may cause aspiration pneumonia.

TEMPERATURE RANGE / RELATIVE HUMIDITY RANGE: Minimum 40° F / R.H. 50%

ALUMINUM: These products are not for use on aluminum unless a minimum of 15 dry mils of epoxy primer is used and a proper amount of zinc anodes. For more information contact your Pro-Line[®] Technical Representative.

STEEL: Prepare surface as per SSPC or NACE Standards, such as SSPC-SP10, NACE 2, SSPC-SP10, NACE 3, SSPC-SP12, NACE 3, SSPC-SP11, Surface Profile Range: 1.5-3.5. After surface preparation apply Pro-Line[®] Epoxy Primers 3000 Series, 4000 Series, 5000 Series, or 4018, giving a total dry mil thickness of at least 15 mils.

WOOD: Over bare wood, primer is not necessary. Apply first coat of anti-fouling thinned 30% with Pro-Line[®] Refinisher #20. Apply second coat unthinned.

LAUNCH TIME: 4 hours minimum after last coat of anti-fouling paint (overnight is recommended). **TUNING:** Not recommended.

This product is effective in preventing marine growth, such as barnacles, bryozoa, etc. Can be used in fresh and salt waters.

NON-PHOTOCHEMICALLY REACTIVE FOR MARINE APPLICATIONS ONLY

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE

Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMAN AND DOMESTIC ANIMALS
HAZARDS TO HUMANS: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately.

HAZARDS TO HUMANS AND DOMESTIC ANIMALS
HAZARDS TO HUMANS: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying another standing boat surface, wear a mask or a respirator jointly approved by the Mining Environment and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes strictly in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE - FLASH POINT APPROXIMATELY 50°F. Keep away from heat and open flame. Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resources Conservation and Recovery Act.

NOTICE: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.