

PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

ACTIVE INGREDIENTS

N,N'-methylenebis (5-methylloxazolidin) 99.09% by wt.

OTHER INGREDIENTS 0.91% by wt.

Total 100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER / PELIGRO

If you do not understand the label, find someone to explain it to you in detail.

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle.

EPA Reg. No. 95475-2-68827 / EPA Est. No. 90928-TX-3

FIRST AID

Call a Poison Control Center or Doctor

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. **If on skin:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor. **If swallowed:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything to an unconscious person. Call a poison control center or doctor. **If inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor.

HOT LINE NUMBER

In case of emergency: Call **1-800-424-9300**. Have the product container or label with you when calling a Poison Control Center, or doctor, or going for treatment. **Note to physician:** Probable mucosal damage may contraindicate the use of gastric lavage.

See back panel for additional precautions and directions for use.

Net Contents: **10 KG (22.04 lb)** Lot #

PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS: Danger. Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wear long-sleeved shirt and long pants, socks, chemical-resistant gloves (such as nitrile or butyl), and protective eyewear. For closed loading systems that are engineered to eliminate contact with aerosols and vapors, workers must have access to a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Keep container closed when not in use. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS: Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

CHEMICAL HAZARDS: Do not mix with strong inorganic acids as this will lead to an excessive release of formaldehyde. Reaction may cause rapid increase of temperature.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage and disposal.

PESTICIDES STORAGE: Keep container closed to prevent spills and contamination. Store in locked/secured area.

PESTICIDE DISPOSAL: Pesticide wastes may be hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

SPILL AND LEAK PROCEDURES: Small releases can be cleaned up using a standard absorbent (i.e. polypads, vermiculite, dry sand). Evacuate immediate area of spill or leak. Place leaking container in well-ventilated area. Identify all sources of ignition before clean-up procedures begin. Wear long-sleeved shirt and long pants or chemical resistant suit, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. Use a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter for entry into affected area. Work upwind if possible. Allow spilled material to evaporate, or absorb onto absorbent material. Neutralize residue with citric acid or other organic neutralizing agent for bases. Test area with litmus paper to ensure neutralization is complete. Thoroughly aerate absorbent materials outdoors prior to disposing on site or at an approved disposal facility. Avoid run-off to storm sewers and ditches leading to natural waterways. Do not allow unprotected persons to enter spill area or clean up area without a respirator until formaldehyde (active constituent of product) levels are determined to be below 0.75 ppm as determined by an OSHA approved method used in accordance with the manufacturer's instructions.

CONTAINER HANDLING: For Commercial Fuel Uses: Nonrefillable container. Do not reuse or refill this container. If empty: Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FUEL PRESERVATION: Predator™ 5000 is recommended for the control of microorganisms for use in closed system diesel fueled vehicles including cars, trucks, marine and freshwater boats. Add Predator™ 5000 to petroleum distillate, biofuel or synthetic, fuel (fuel grades boiling point below 390°C) in fuel tanks. Predator™ 5000 must be added, as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated fuel system. For best performance, provide good distribution of Predator™ 5000 in the fuel by mixing or by adding the biocide before or during tank filling. Product dispersion can be enhanced by running engine to ensure thorough mixing. Furthermore Predator™ 5000 must remain in contact with treated fuel system for a minimum of four hours and preferably eight hours to decontaminate the fuel and fuel system walls.

SMALL FUEL SYSTEMS (less than 100 gallons of fuel): For shock-treatment of heavily contaminated fuel systems, add 6 to 13 ounces of Predator™ 5000 per 100 gal of fuel to achieve a concentration of 500 to 1000 ppm (v/v) in the treated fuel system.

FOR TREATMENT OF MODERATELY CONTAMINATED FUEL SYSTEMS: Add 3 to 6 ounces of Predator™ 5000 to 100 gal of fuel to achieve a concentration of 200 – 500 ppm (v/v).

FOR PREVENTIVE TREATMENT: Add 1 to 3 ounces of Predator™ 5000 to 100 gal of fuel to achieve a concentration of 50 to 200 ppm (v/v).

LIMITED WARRANTY: Manufacturer warrants that this product is suited for the labeled use when applied according to label directions. To the extent consistent with applicable laws, manufacturer makes no warranty of merchantability. To the extent consistent with applicable laws there are no warranties that extend beyond the description on this label and in no event shall the manufacturer be liable for any consequential damages.



innospec

Distributed by: Innospec Fuel Specialties LLC
8310 South Valley Hwy, #350, Englewood, CO 80112
(303) 792-5554 or 1-800-441-9547
Product Information: 800-441-9547



PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

ACTIVE INGREDIENTS

N,N'-methylenebis (5-methyloxazolidin)	99.09% by wt.
OTHER INGREDIENTS	0.91% by wt.
	Total 100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER / PELIGRO

If you do not understand the label, find someone to explain it to you in detail. / Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle.
EPA Reg. No. 95475-2-68827 / EPA Est. No. 90928-TX-3

FIRST AID

First Aid - Call a Poison Control Center or Doctor

- If in eyes:** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. - Call a poison control center or doctor.
- If on skin:** - Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor.
- If swallowed:** - Call a poison control center or doctor immediately for treatment advice. - Have person sip a glass of water if able to swallow. - Do not induce vomiting unless told to by a poison control center or doctor. - Do not give anything to an unconscious person. - Call a poison control center or doctor.
- If inhaled:** - Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible - Call a poison control center or doctor.

HOT LINE NUMBER

In case of emergency: call **1-800-424-9300**. Have the product container or label with you when calling a Poison Control Center, or doctor, or going for treatment.

Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.

See back panel for additional precautions and directions for use.

Net Contents: **32 ounces (946 ml)** Lot #





PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS: Danger. Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wear long-sleeved shirt and long pants, socks, chemical-resistant gloves (such as nitrile or butyl), and protective eyewear. For closed loading systems that are engineered to eliminate contact with aerosols and vapors, workers must have access to a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Keep container closed when not in use. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS: Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

CHEMICAL HAZARDS: Do not mix with strong inorganic acids as this will lead to an excessive release of formaldehyde. Reaction may cause rapid increase of temperature.



See directions for use on enclosed brochure.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage and disposal.

PESTICIDES STORAGE: Keep container closed to prevent spills and contamination. Store in locked/secured area.

PESTICIDE DISPOSAL: Pesticide wastes may be hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

SPILL AND LEAK PROCEDURES: Small releases can be cleaned up using a standard absorbent (i.e. polypads, vermiculite, dry sand). Evacuate immediate area of spill or leak. Place leaking container in well-ventilated area. Identify all sources of ignition before clean-up procedures begin. Wear long-sleeved shirt and long pants or chemical resistant suit, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. Use a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter for entry into affected area. Work upwind if possible. Allow spilled material to evaporate, or absorb onto absorbent material. Neutralize residue with citric acid or other organic neutralizing agent for bases. Test area with litmus paper to ensure neutralization is complete. Thoroughly aerate absorbent materials outdoors prior to disposing on site or at an approved disposal facility. Avoid run-off to storm sewers and ditches leading to natural waterways. Do not allow unprotected persons to enter spill area or clean up area without a respirator until formaldehyde (active constituent of product) levels are determined to be below 0.75 ppm as determined by an OSHA approved method used in accordance with the manufacturer's instructions.

CONTAINER HANDLING: For Commercial Fuel Uses: Nonrefillable container. Do not reuse or refill this container. If empty: Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

innospec

Distributed by: Innospec Fuel Specialties LLC
8310 South Valley Hwy, #350, Englewood, CO 80112
(303) 792-5554 or 1-800-441-9547
Product Information: 800-441-9547

LIFT HERE



PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FUEL PRESERVATION: Predator™ 5000 is recommended for the control of microorganisms for use in closed system diesel fueled vehicles including cars, trucks, marine and freshwater boats. Add Predator™ 5000 to petroleum distillate, biofuel or synthetic, fuel (fuel grades boiling point below 390°C) in fuel tanks. Predator™ 5000 must be added, as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated fuel system. For best performance, provide good distribution of Predator™ 5000 in the fuel by mixing or by adding the biocide before or during tank filling. Product dispersion can be enhanced by running engine to ensure thorough mixing. Furthermore Predator™ 5000 must remain in contact with treated fuel system for a minimum of four hours and preferably eight hours to decontaminate the fuel and fuel system walls.

SMALL FUEL SYSTEMS (less than 100 gallons of fuel): For shock-treatment of heavily contaminated fuel systems, add 6 to 13 ounces of Predator™ 5000 per 100 gal of fuel to achieve a concentration of 500 to 1000 ppm (v/v) in the treated fuel system.

FOR TREATMENT OF MODERATELY CONTAMINATED FUEL SYSTEMS: Add 3 to 6 ounces of Predator™ 5000 to 100 gal of fuel to achieve a concentration of 200 – 500 ppm (v/v).

FOR PREVENTIVE TREATMENT: Add 1 to 3 ounces of Predator™ 5000 to 100 gal of fuel to achieve a concentration of 50 to 200 ppm (v/v).

LIMITED WARRANTY: Manufacturer warrants that this product is suited for the labeled use when applied according to label directions. To the extent consistent with applicable laws, manufacturer makes no warranty of merchantability. To the extent consistent with applicable laws there are no warranties that extend beyond the description on this label and in no event shall the manufacturer be liable for any consequential damages.

PREDATOR™ 5000

Industrial Microbiocide for Use in Fuels

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS: Danger. Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wear long-sleeved shirt and long pants, socks, chemical-resistant gloves (such as nitrile or butyl), and protective eyewear. For closed loading systems that are engineered to eliminate contact with aerosols and vapors, workers must have access to a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Keep container closed when not in use. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS: Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, or oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

CHEMICAL HAZARDS: Do not mix with strong inorganic acids as this will lead to an excessive release of formaldehyde. Reaction may cause rapid increase of temperature.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage and disposal.

PESTICIDE DISPOSAL: Keep container closed to prevent spills and contamination. Store in locked/secured area.

PESTICIDE DISPOSAL: Pesticide wastes may be hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

SPILL AND LEAK PROCEDURES: Small releases can be cleaned up using a standard absorbent (i.e. polypads, vermiculite, dry sand). Evacuate immediate area of spill or leak. Place leaking container in well-ventilated area. Identify all sources of ignition before clean up procedures begin. Wear long-sleeved shirt and long pants or chemical resistant suit, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. Use a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter for entry into affected area. Work upwind if possible. Allow spilled material to evaporate, or absorb onto absorbent material. Neutralize residue with citric acid or other organic neutralizing agent for bases. Test area with litmus paper to ensure neutralization is complete. Thoroughly aerate absorbent materials outdoors prior to disposing on site or at an approved disposal facility. Avoid run-off to storm sewers and ditches leading to natural waterways. Do not allow unprotected persons to enter spill area or clean up area without a respirator until formaldehyde (active constituent of product) levels are determined to be below 0.75 ppm as determined by an OSHA approved method used in accordance with the manufacturer's instructions.

CONTAINER HANDLING: For Commercial Fuel Uses: Nonrefillable container. Do not reuse or refill this container. If empty: Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.



innospec

Distributed by: Innospec Fuel Specialties LLC
8310 South Valley Hwy, # 350, Englewood, CO 80112
(303) 792-5554 or 1-800-441-9547
Product Information: 800-441-9547



Industrial microbiocide for use in fuels
Industrial microbiocide for use in oilfield equipment and fluids

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FOR USE IN: FUEL PRESERVATION

Predator™ 5000 is recommended for the control of microorganisms for use in closed system diesel fueled vehicles including cars, trucks, marine and freshwater boats.

Add Predator™ 5000 to petroleum distillate, biofuel or synthetic, fuel (fuel grades boiling point below 390°C) in fuel tanks. Predator™ 5000 must be added, as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated fuel system.

For best performance, provide good distribution of Predator™ 5000 in the fuel by mixing or by adding the biocide before or during tank filling. Product dispersion can be enhanced by running engine to ensure thorough mixing. Furthermore Predator™ 5000 must remain in contact with treated fuel system for a minimum of four hours and preferably eight hours to decontaminate the fuel and fuel system walls.

Large Fuel Systems (greater than 1000 gallons of fuel)

For shock-treatment of heavily contaminated fuel systems, add 0.5 to 1 gal of Predator™ 5000 per 1000 gal of fuel and fuel associated water to achieve a concentration of 500 to 1000 ppm (v/v) in the treated fuel system.

For treatment of moderately contaminated fuel systems, add 0.2 gal to 0.5 gal of Predator™ 5000 to 1000 gal of fuel to achieve a concentration of 200 – 500 ppm (v/v).

For preventive treatment, add 0.05 to 0.2 gal (6.4 to 26 oz) of Predator™ 5000 to 1000 gal of fuel to achieve a concentration of 50 to 200 ppm (v/v).

FOR USE IN: OILFIELD EQUIPMENT AND FLUIDS MICROORGANISM CONTROL

Predator™ 5000 is recommended for the control of microorganisms in oil and gas operating systems. Predator™ 5000 is recommended for controlling the growth of bacteria and fungi in dispersed and free-water commonly found in oil and gas operational systems.

Add Predator™ 5000 to drilling fluids, workover fluids, well completion fluids, packer fluids, hydraulic fracturing fluids, hydrotest fluids in closed system tanks and pipelines via closed system dosing. Predator™ 5000 must be added, through a closed system as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated system. Add 0.5 to 1 gal of Predator™ 5000 per 1000 gal of fluid to achieve a concentration of 500 to 1000 ppm (v/v) in the treated system.

For preventive treatment, depending on frequency of treatment add 0.2 to 1 gal of Predator™ 5000 to 1000 gal of fluid to achieve a concentration of 200 to 1000 ppm (v/v).

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Keep container closed to prevent spills and contamination. Store in locked/secured area.

Pesticide Disposal: Pesticide wastes may be hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Spill and Leak Procedures: Small releases can be cleaned up using a standard absorbent (i.e. polypads,vermiculite, dry sand). Evacuate immediate area of spill or leak. Place leaking container in well-ventilated area. Identify all sources of ignition before clean-up procedures begin. Wear long-sleeved shirt and long pants or chemical resistant suit, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. Use a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter for entry into affected area. Work upwind if possible. Allow spilled material to evaporate, or absorb onto absorbent material. Neutralize residue with citric acid or other organic neutralizing agent for bases. Test area with litmus paper to ensure neutralization is complete. Thoroughly aerate absorbent materials outdoors prior to disposing on site or at an approved disposal facility. Avoid run-off to storm sewers and ditches leading to natural waterways. Do not allow unprotected persons to enter spill area or clean up area without a respirator until formaldehyde (active constituent of product) levels are determined to be below 0.75 ppm as determined by an OSHA approved method used in accordance with the manufacturer’s instructions.

CONTAINER HANDLING

For Commercial Fuel Uses: Nonrefillable container. Do not reuse or refill this container. If empty: Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

For Commercial Oilfield Uses: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

LIMITED WARRANTY

Manufacturer warrants that this product is suited for the labeled use when applied according to label directions. To the extent consistent with applicable laws, manufacturer makes no warranty of merchantability. To the extent consistent with applicable laws there are no warranties that extend beyond the description on this label and in no event shall the manufacturer be liable for any consequential damages.

Distributed by: Innospec Fuel Specialties LLC

8310 South Valley Highway, Suite 350, Englewood, Colorado 80112
(303) 792-5554 or 1-800-441-9547

Product Information: 800-441-9547



Predator™ 5000

ACTIVE INGREDIENTS

N,N'-methylenebis (5-methylloxazolidin).....99.09% by wt.

OTHER INGREDIENTS.....0.91% by wt.

Total 100.00%

FIRST AID – Call a Poison Control Center or Doctor	
IF IN EYES:	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. - Call a poison control center or doctor.
IF ON SKIN:	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor.
IF SWALLOWED:	- Call a poison control center or doctor immediately for treatment advice. - Have person sip a glass of water if able to swallow. - Do not induce vomiting unless told to by a poison control center or doctor. - Do not give anything to an unconscious person. - Call a poison control center or doctor.
IF INHALED:	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible - Call a poison control center or doctor.
HOT LINE NUMBER	
IN CASE OF AN EMERGENCY , call 1-800-424-9300. Have the product container or label with you when calling a Poison Control Center, or doctor, or going for treatment.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	

KEEP OUT OF REACH OF CHILDREN DANGER PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER: Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wear long-sleeved shirt and long pants, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. For closed loading systems that are engineered to eliminate contact with aerosols and vapors, workers must have access to a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Keep container closed when not in use. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

CHEMICAL HAZARDS

Do not mix with strong inorganic acids as this will lead to an excessive release of formaldehyde. Reaction may cause rapid increase of temperature.

EPA Reg. No: 95475-2-68827

Net Contents: 450 lbs. (204.3 kgs.) / 55 Gall

EPA Est. No: 90928-TX-3

Lot#



- Industrial microbiocide for use in fuels, - Industrial microbiocide for use in oilfield equipment and fluids

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FOR USE IN: FUEL PRESERVATION

Predator™ 5000 is recommended for the control of microorganisms for use in closed system diesel fueled vehicles including cars, trucks, marine and freshwater boats.

Add Predator™ 5000 to petroleum distillate, biofuel or synthetic, fuel (fuel grades boiling point below 390°C) in fuel tanks. Predator™ 5000 must be added, as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated fuel system.

For best performance, provide good distribution of Predator™ 5000 in the fuel by mixing or by adding the biocide before or during tank filling. Product dispersion can be enhanced by running engine to ensure thorough mixing. Furthermore Predator™ 5000 must remain in contact with treated fuel system for a minimum of four hours and preferably eight hours to decontaminate the fuel and fuel system walls.

Large Fuel Systems (greater than 1000 gallons of fuel)

For shock-treatment of heavily contaminated fuel systems, add 0.5 to 1 gal of Predator™ 5000 per 1000 gal of fuel and fuel associated water to achieve a concentration of 500 to 1000 ppm (v/v) in the treated fuel system.

For treatment of moderately contaminated fuel systems, add 0.2 gal to 0.5 gal of Predator™ 5000 to 1000 gal of fuel to achieve a concentration of 200 – 500 ppm (v/v).

For preventive treatment, add 0.05 to 0.2 gal (6.4 to 26 oz) of Predator™ 5000 to 1000 gal of fuel to achieve a concentration of 50 to 200 ppm (v/v).

FOR USE IN: OILFIELD EQUIPMENT AND FLUIDS MICROORGANISM CONTROL

Predator™ 5000 is recommended for the control of microorganisms in oil and gas operating systems. Predator™ 5000 is recommended for controlling the growth of bacteria and fungi in dispersed and free-water commonly found in oil and gas operational systems.

Add Predator™ 5000 to drilling fluids, workover fluids, well completion fluids, packer fluids, hydraulic fracturing fluids, hydrotest fluids in closed system tanks and pipelines via closed system dosing. Predator™ 5000 must be added, through a closed system as a single dose or by proportional metering to achieve the appropriate Predator™ 5000 concentration in the treated system. Add 0.5 to 1 gal of Predator™ 5000 per 1000 gal of fluid to achieve a concentration of 500 to 1000 ppm (v/v) in the treated system.

For preventive treatment, depending on frequency of treatment add 0.2 to 1 gal of Predator™ 5000 to 1000 gal of fluid to achieve a concentration of 200 to 1000 ppm (v/v).

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Keep container closed to prevent spills and contamination. Store in locked/secured area.

Pesticide Disposal: Pesticide wastes may be hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Spill and Leak Procedures: Small releases can be cleaned up using a standard absorbent (i.e. polypads,vermiculite, dry sand). Evacuate immediate area of spill or leak. Place leaking container in well-ventilated area. Identify all sources of ignition before clean-up procedures begin. Wear long-sleeved shirt and long pants or chemical resistant suit, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. Use a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter for entry into affected area. Work upwind if possible. Allow spilled material to evaporate, or absorb onto absorbent material. Neutralize residue with citric acid or other organic neutralizing agent for bases. Test area with litmus paper to ensure neutralization is complete. Thoroughly aerate absorbent materials outdoors prior to disposing on site or at an approved disposal facility. Avoid run-off to storm sewers and ditches leading to natural waterways. Do not allow unprotected persons to enter spill area or clean up area without a respirator until formaldehyde (active constituent of product) levels are determined to be below 0.75 ppm as determined by an OSHA approved method used in accordance with the manufacturer’s instructions.

CONTAINER HANDLING

For Commercial Fuel Uses: Nonrefillable container. Do not reuse or refill this container. If empty: Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

For Commercial Oilfield Uses: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

LIMITED WARRANTY

Manufacturer warrants that this product is suited for the labeled use when applied according to label directions. To the extent consistent with applicable laws, manufacturer makes no warranty of merchantability. To the extent consistent with applicable laws there are no warranties that extend beyond the description on this label and in no event shall the manufacturer be liable for any consequential damages.

Distributed by: Innospec Fuel Specialties LLC

8310 South Valley Highway, Suite 350, Englewood, Colorado 80112
(303) 792-5554 or 1-800-441-9547

Product Information: 800-441-9547



Predator™ 5000

ACTIVE INGREDIENTS

N,N'-methylenebis (5-methyloxazolidin).....99.09% by wt.

OTHER INGREDIENTS.....0.91% by wt.

Total 100.00%

FIRST AID – Call a Poison Control Center or Doctor	
IF IN EYES:	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. - Call a poison control center or doctor.
IF ON SKIN:	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor.
IF SWALLOWED:	- Call a poison control center or doctor immediately for treatment advice. - Have person sip a glass of water if able to swallow. - Do not induce vomiting unless told to by a poison control center or doctor. - Do not give anything to an unconscious person. - Call a poison control center or doctor.
IF INHALED:	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible - Call a poison control center or doctor.
HOT LINE NUMBER	
IN CASE OF AN EMERGENCY , call 1-800-424-9300. Have the product container or label with you when calling a Poison Control Center, or doctor, or going for treatment.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	

KEEP OUT OF REACH OF CHILDREN DANGER PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wear long-sleeved shirt and long pants, socks, chemical resistant gloves (such as nitrile or butyl), and protective eyewear. For closed loading systems that are engineered to eliminate contact with aerosols and vapors, workers must have access to a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C) or a canister approved for pesticides (NIOSH approval number prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Keep container closed when not in use. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

CHEMICAL HAZARDS

Do not mix with strong inorganic acids as this will lead to an excessive release of formaldehyde. Reaction may cause rapid increase of temperature.

EPA Reg. No: 95475-2-68827

Net Contents: 2168 lbs. (983.39 kgs.) / 265 Gals

EPA Est. No: 90928-TX-3

Lot#